

## FEATURES

- 2<sup>nd</sup> Generation S-LOCK Securing System
- Unique rotary switch and low profile C15 locking mechanism fits any standard C14 and C16 inlet
- Rated up to 15 Amps
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DISCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz); 500VDC (1min)
Rating	UL/cUL : 10A/13A/15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-25°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG For Europe : 0.75mm <sup>2</sup> / 1.0 mm <sup>2</sup>

## COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS



## ORDERING INFORMATION

**514850 - XX XYZ X**

### S-Lock Series No.

#### WIRE TYPE:

##### For North America:

94=18AWG/SVT, 95=18AWG/SJT  
85=16AWG/SJT, 75=14AWG/SJT

##### For Europe:

13=0.75mm<sup>2</sup>/H05VV-F, 23=1.0mm<sup>2</sup>/H05VV-F

#### CABLE LENGTH:

For North America: XY=feet, Z=inch  
For Europe: X=meter, YZ=cm

### Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White