

FEATURES

- **2nd Generation S-LOCK Securing System**
- **Unique rotary switch and low profile C19 locking mechanism fits any standard C20 inlet**
- **Rated up to 20 Amps**
- **Various colors / length available**



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 15A/20A 250VAC TUV or VDE : 16A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 14AWG / 12AWG For Europe : 1.5mm ² / 2.5 mm ²

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION

520890 – XX XYZ X










S-Lock Series No.

WIRE TYPE:
For North America:
75=14AWG/SJT, 65=12AWG/SJT

For Europe:
33=1.5mm²/H05VV-F, 53=2.5 mm²/H05VV-F,

CABLE LENGTH:
For North America: XY=feet, Z=inch
For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)

 0=Black	 1=Gray	 2=Blue
 3=Purple	 4=Green	 6=Orange
 7=Red	 8=Yellow	 9=White