# C-Lock 55239X SERIES - NEMA 5-20P

# SSEMCO

# **FEATURES**

- Revolutionary cable securing C-Lock system prevents unintentional power disconnection.
- Standard NEMA 5-20 plug for conventional power outlets across North America.
- Hospital Grade NEMA 5-20 plug with green dot for medical equipments.
- Patented C19 C-Lock functions with C-Lock C20 inlets.
- Rated up to 20 amps.
- Various colors / lengths available.



### TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL 817/UL 498
High Potential Test Voltage	2000VAC (1min 50Hz)
Rating	UL/cUL: 10A/13A/20A 125VAC
Operation Temperature	-25°C ~ +70°C
Flammability Corresponding to	Plug: UL 94V-2 or better; Cable: UL VW-1
Cable Option	14AWG 3G SJT
	12AWG 3G SJT

#### **COMMON APPLICATIONS**

- Data Centers
- Medical Devices
- Automation Industry
- Industrial Equipment
- Architectural Devices
- Broadcasting Stations
- Critical Power Management

**APPROVALS** 







# ORDERING INFORMATION

5 52 39 X - XX XYZ X

## PLUG TYPE:

0= Straight NEMA 5-20P

H= Hospital Grade NEMA 5-20P









# **COLOR CODE:**

0=Black, 1=Gray, 2=Blue, 4=Green, 6=Orange, 7=Red, 8=Yellow, 9=White

**CABLE LENGTH:** 

XY=feet, Z=inch

**WIRE TYPE:** 

75=14AWG/SJT, 65=12AWG/SJT