# C-Lock 56139X SERIES - NEMA 6-15P

# SSEMCO

# **FEATURES**

- Revolutionary cable securing C-Lock system prevents unintentional power disconnection.
- Standard NEMA 6-15 plug for conventional power outlets across North America.
- Hospital Grade NEMA 6-15 plug with green dot for medical equipments.
- Patented C19 C-Lock functions with C-Lock C20 inlets.
- Rated up to 15 amps.
- · Various colors / lengths available.



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL 817/UL 498
High Potential Test Voltage	2000VAC (1min 50Hz)
Rating	UL/cUL: 10A/13A/15A 250VAC
Operation Temperature	-25°C ~ +70°C
Flammability Corresponding to	Plug: UL 94V-2 or better; Cable: UL VW-1
Cable Option	18AWG 3G SVT and SJT
	16AWG 3G SJT
	14AWG 3G SJT

#### **COMMON APPLICATIONS**

- Data Centers
- Medical Devices
- Automation Industry
- Industrial Equipment
- Architectural Devices
- Broadcasting Stations
- Critical Power Management

**APPROVALS** 







# ORDERING INFORMATION

5 61 39 X - XX XYZ X

#### **PLUG TYPE:**

0= Straight NEMA 6-15P

H= Hospital Grade NEMA 6-15P









### **COLOR CODE:**

0=Black, 1=Gray, 2=Blue, 4=Green, 6=Orange, 7=Red, 8=Yellow, 9=White

**CABLE LENGTH:** 

XY=feet, Z=inch

#### WIRE TYPE:

94=18AWG/SVT, 95=18AWG/SJT, 85=16AWG/SJT, 75=14AWG/SJT