

FEATURES:

- Double row high density design
- 2x2 and 2x3 outlets available
- Patented C13 positive mechanical locks with SSEMCO P-Lock lite plug and is backward compatible with any standard C14 plug
- Rated UL94V-0 & Halogen-Free
- Various color available
- Multi panel thickness design



P-Lock Ready



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION	DIMENSIONS (UNIT: mm)	
Standard	IEC 60320-2-2 Sheet F	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>R62374 Series</p> </div> <div style="text-align: center;"> <p>R62376 Series</p> </div> </div> <div style="text-align: right; margin-top: 10px;"> </div>	
Dielectric Strength	2000VAC (1min 50Hz)		
Insulation Resistance	Over 100MΩ at 500V DC		
Material	PC 94V-0, Halogen-free		
Panel Thickness	1.0~1.7mm		
Rating	UL: 15A 250VAC TUV:10A 250VAC		
Operation Temperature	-5°C ~ +70°C		
Approvals	For North America: UL60320 Certified by UL		
	For Europe: IEC60320 Certified by TUV		

ORDERING INFORMATION

4-GANG P/N:

R62374-34YY00 (YY=COLORD CODE)

6-GANG P/N:

R62376-36YY00 (YY=COLORD CODE)

Color Code: YY=

 55=Black	 11=Gray	 22=Blue
 88=Violet	 44=Green	 66=Orange
 77=Red	 33=Brown	 99=White

*Actual color may vary.