

## FEATURES

- 2<sup>nd</sup> Generation S-Lock® Securing System
- Patented low profile C13 rotary locking system fits any standard C14 inlet
- Up to 15 Amps Current Rating
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Current and voltage rating	UL/cUL : 10A/13A/15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor size option	For North America : 18AWG / 16AWG / 14AWG For Europe : 0.75mm <sup>2</sup> / 1.0 mm <sup>2</sup>

### COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

## APPROVALS



## ORDERING INFORMATION

**514830 - XX XYZ X**

S-Lock® Series No.

### WIRE TYPE:

For North America:

94=18AWG/SVT, 95=18AWG/SJT

85=16AWG/SJT, 75=14AWG/SJT

For Europe:

13=0.75mm<sup>2</sup>/H05VV-F, 23=1.0mm<sup>2</sup>/H05VV-F

### CABLE LENGTH:

For North America: XY=feet, Z=inch

For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White