

FEATURES

- 2nd Generation S-Lock® Securing System
- Patented low profile C13 rotary locking system fits any standard C14 inlet
- Up to 15 Amps Current Rating
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Current and Voltage Rating	UL/cUL : 15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor Size Option	For North America : 14AWG For Europe : 1.5 mm ²

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

APPROVALS



ORDERING INFORMATION

520830 - XX XYZ X

S-Lock® Series No.

WIRE TYPE:

For North America:
75=14AWG/SJT

For Europe:
33=1.5mm²/H05VV-F

CABLE LENGTH:

For North America: XY=feet, Z=inch
For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White