

FEATURES

- 2nd Generation S-Lock® Securing System
- Patented low profile C19 rotary locking system fits any standard C20 inlet
- Fully compliance with UL60320
- Standard NEMA 5-15 plug for conventional power outlets across North America
- Up to 15 Amps Current Rating
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL817 / UL 60320
High potential test voltage	1250VAC (1min 50Hz)
Current and voltage rating	UL/cUL : 15A 125VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor Size Option	For North America : 14AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

APPROVALS



ORDERING INFORMATION

551890 - XX XYZ X

S-Lock® Series No.

WIRE TYPE:
For North America:
75=14AWG/SJT

CABLE LENGTH:
For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White