

## FEATURES

- Revolutionary positive securing system prevents unintentional power disconnection
- Patented C14 locking mechanism is compatible with SSEMCO® P-Lock® outlets and supports interoperability with any standard C13 outlet
- Fit for high density multi-outlets design
- Multi-angle plug option
- Up to 15 Amps Current Rating
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Current and voltage rating	North America : 15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor Size Option	For North America : 14AWG

## COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

## APPROVALS



## ORDERING INFORMATION

**61419X - XX XYZ X**

**Plug Angle Option**

0=Straight    1=Right    2=Left

3=Up    4=Down

**Color Options: (Actual color may vary)**

0=Black    1=Gray    2=Blue

3=Purple    4=Green    6=Orange

7=Red    8=Yellow    9=White

**WIRE TYPE:**  
For North America : 75=14AWG/SJT

**CABLE LENGTH:**  
For North America: XY=feet, Z=inch  
For Europe: X=meter, YZ=cm