

FEATURES

- Revolutionary positive securing system prevents unintentional power disconnection
- Patented C20 positive mechanism locks with SSEMCO® P-Lock® outlets and is backward compatible with any standard C19 outlet
- Fit for high density multi-outlets design
- Multi-angle plug option
- Rated up to 15 Amps
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Current and voltage rating	North America : 15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor Size Option	For North America : 14AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management



ORDERING INFORMATION

62015X - XX XYZ X

Plug Angle Option

0=Straight 1=Right 2=Left
3=Up 4=Down

Color Options: (Actual color may vary)

0=Black 1=Gray 2=Blue
3=Purple 4=Green 6=Orange
7=Red 8=Yellow 9=White

WIRE TYPE:
For North America: 75=14AWG/SJT

CABLE LENGTH:
For North America: XY=feet, Z=inch
For Europe: X=meter, YZ=cm