

FEATURES

- 2nd Generation Dual-Lock® Securing System
- Patented low profile C21 rotary locking system fits any standard C22/C20 inlet
- Patented C20 locking mechanism is compatible with SSEMCO® P-Lock® outlets and supports interoperability with any standard C19 outlet
- Temperature resistance of C21 up to 155°C
- Up to 20 Amp Current Rating
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Current and voltage rating	UL/cUL : 15A/20A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better
Conductor size option	For North America : 14AWG / 12AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

APPROVALS



ORDERING INFORMATION

62081X - XX XYZ X

Plug Angle Option

0=Straight 1=Right 2=Left
3=Up 4=Down

Color Options: (Actual color may vary)

0=Black 1=Gray 2=Blue
3=Purple 4=Green 6=Orange
7=Red 8=Yellow 9=White

WIRE TYPE:
For North America:
75=14AWG/SJT, 65=12AWG/SJT

CABLE LENGTH:
For North America: XY=feet, Z=inch