

## FEATURES

- 2<sup>nd</sup> Generation Dual-Lock® Securing System
- Patented low profile C19 rotary locking system fits any standard C20 inlet
- Patented C20 locking mechanism is compatible with SSEMCO® P-Lock® outlets and supports interoperability with any standard C19 outlet
- Up to 20 Amps Current Rating
- Various colors / length available



## TECHNICAL SPECIFICATIONS

| SPECIFICATION                 | DESCRIPTION  |
|-------------------------------|--|
| Standard                      | IEC 60320  |
| High potential test voltage   | 2000VAC (1min 50Hz)  |
| Current and voltage rating    | UL/cUL : 15A/20A 250VAC<br>TUV or VDE : 16A 250VAC   |
| Operation temperature         | -20°C ~ +70°C  |
| Flammability corresponding to | Plug/Connector: UL 94V-2 or better   |
| Conductor size option         | For North America : 14AWG / 12AWG<br>For Europe : 1.5mm <sup>2</sup> / 2.5 mm <sup>2</sup> |

## COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation industry
- Industrial equipment
- Architectural devices
- Broadcasting stations
- Critical power management

## APPROVALS




## ORDERING INFORMATION

### Plug Angle Option


Angle options are only available for UL



0=Straight



1=Right



2=Left



3=Up



4=Down

### WIRE TYPE:

For North America:

75=14AWG/SJT, 65=12AWG/SJT

For Europe:

33=1.5mm<sup>2</sup>/H05VV-F, 53=2.5mm<sup>2</sup>/H05VV-F

### 62089X - XX XYZ X

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White

### CABLE LENGTH:

For North America: XY=feet, Z=inch

For Europe: X=meter, YZ=cm